

class GTK::V3::Gtk::GtkAboutDialog

Table of Contents

- 1 [Synopsis](#)
- 2 [Types](#)
- 2.1 [enum GtkLicense](#)
- 3 [Methods](#)
 - 3.1 [gtk_about_dialog_new](#)
 - 3.2 [\[gtk_about_dialog_\] get_program_name](#)
 - 3.3 [\[gtk_about_dialog_\] set_program_name](#)
 - 3.4 [\[gtk_about_dialog_\] get_version](#)
 - 3.5 [\[gtk_about_dialog_\] set_version](#)
 - 3.6 [\[gtk_about_dialog_\] get_copyright](#)
 - 3.7 [\[gtk_about_dialog_\] set_copyright](#)
 - 3.8 [\[gtk_about_dialog_\] get_comments](#)
 - 3.9 [\[gtk_about_dialog_\] set_comments](#)
 - 3.10 [\[gtk_about_dialog_\] get_license](#)
 - 3.11 [\[gtk_about_dialog_\] set_license](#)
 - 3.12 [\[gtk_about_dialog_\] get_wrap_license](#)
 - 3.13 [\[gtk_about_dialog_\] set_wrap_license](#)
 - 3.14 [\[gtk_about_dialog_\] get_license_type](#)
 - 3.15 [\[gtk_about_dialog_\] set_license_type](#)
 - 3.16 [\[gtk_about_dialog_\] get_website](#)
 - 3.17 [\[gtk_about_dialog_\] set_website](#)
 - 3.18 [\[gtk_about_dialog_\] get_website_label](#)
 - 3.19 [\[gtk_about_dialog_\] set_website_label](#)
 - 3.20 [\[gtk_about_dialog_\] get_authors](#)
 - 3.21 [\[gtk_about_dialog_\] set_authors](#)
 - 3.22 [\[gtk_about_dialog_\] get_artists](#)
 - 3.23 [\[gtk_about_dialog_\] set_artists](#)
 - 3.24 [\[gtk_about_dialog_\] get_documenters](#)
 - 3.25 [\[gtk_about_dialog_\] set_documenters](#)
 - 3.26 [\[gtk_about_dialog_\] get_translator_credits](#)
 - 3.27 [\[gtk_about_dialog_\] set_translator_credits](#)
 - 3.28 [\[gtk_about_dialog_\] get_logo](#)
 - 3.29 [\[gtk_about_dialog_\] set_logo](#)
 - 3.30 [\[gtk_about_dialog_\] get_logo_icon_name](#)
 - 3.31 [\[gtk_about_dialog_\] set_logo_icon_name](#)
 - 3.32 [\[gtk_about_dialog_\] add_credit_section](#)
 - 3.33 [new](#)

```
unit class GTK::V3::Gtk::GtkAboutDialog;  
also is GTK::V3::Gtk::GtkDialog;
```

Synopsis

```
my GTK::V3::Gtk::GtkAboutDialog $about .= new(:empty);  
$about.set-program-name('My-First-GTK-Program');  
  
# show the dialog  
$about.gtk-dialog-run;  
  
# when dialog buttons are pressed control returns here. Hide the dialog again  
$about.gtk-widget-hide;
```

Types

enum GtkLicense

A series of names to set the license type.

License type	License
GTK_LICENSE_UNKNOWN	No license specified
GTK_LICENSE_CUSTOM	A license text is going to be specified by the developer
GTK_LICENSE_GPL_2_0	The GNU General Public License, version 2.0 or later
GTK_LICENSE_GPL_3_0	The GNU General Public License, version 3.0 or later
GTK_LICENSE_LGPL_2_1	The GNU Lesser General Public License, version 2.1 or later
GTK_LICENSE_LGPL_3_0	The GNU Lesser General Public License, version 3.0 or later
GTK_LICENSE_BSD	The BSD standard license
GTK_LICENSE_MIT_X11	The MIT/X11 standard license
GTK_LICENSE_ARTISTIC	The Artistic License, version 2.0
GTK_LICENSE_GPL_2_0_ONLY	The GNU General Public License, version 2.0 only. Since 3.12.
GTK_LICENSE_GPL_3_0_ONLY	The GNU General Public License, version 3.0 only. Since 3.12.
GTK_LICENSE_LGPL_2_1_ONLY	The GNU Lesser General Public License, version 2.1 only. Since 3.12.
GTK_LICENSE_LGPL_3_0_ONLY	The GNU Lesser General Public License, version 3.0 only. Since 3.12.
GTK_LICENSE_AGPL_3_0	The GNU Affero General Public License, version 3.0 or later. Since: 3.22.
GTK_LICENSE_AGPL_3_0_ONLY	The GNU Affero General Public License, version 3.0 only. Since: 3.22.27.

See [gtk_about_dialog_get_license_type](#) for an example.

Methods

gtk_about_dialog_new

```
method gtk_about_dialog_new ( --> N-GObject )
```

Creates a new empty about dialog widget. It returns a native object which must be stored in another object. Better, shorter and easier is to use `.new(:empty)`. See info below.

[gtk_about_dialog_] get_program_name

```
method gtk_about_dialog_get_program_name ( --> Str )
```

Get the program name from the dialog.

[gtk_about_dialog_] set_program_name

```
method gtk_about_dialog_set_program_name ( Str $pname )
```

Set the program name in the about dialog.

[gtk_about_dialog_] get_version

```
method gtk_about_dialog_get_version ( --> Str )
```

Get the version.

[gtk_about_dialog_] set_version

```
method gtk_about_dialog_set_version ( Str $version )
```

Set version.

[gtk_about_dialog_] get_copyright

```
method gtk_about_dialog_get_copyright
```

Get copyright.

[gtk_about_dialog_] set_copyright

```
method gtk_about_dialog_set_copyright
```

Set copyright.

[gtk_about_dialog_] get_comments

```
method gtk_about_dialog_get_comments
```

Get comments.

[gtk_about_dialog_] set_comments

```
method gtk_about_dialog_set_comments
```

Set comments.

[gtk_about_dialog_] get_license

```
method gtk_about_dialog_get_license
```

Get license.

[gtk_about_dialog_] set_license

```
method gtk_about_dialog_set_license
```

Set license.

[gtk_about_dialog_] get_wrap_license

```
method gtk_about_dialog_get_wrap_license
```

Return 1 if license is wrapped.

[gtk_about_dialog_] set_wrap_license

```
method gtk_about_dialog_set_wrap_license
```

Sets whether the license text in about is automatically wrapped. This is only done when license type is [GTK_LICENSE_CUSTOM](#). See also [gtk_about_dialog_get_license_type](#). P.s. I didn't see much difference between wrapped or unwrapped.

[gtk_about_dialog_] get_license_type

```
method gtk_about_dialog_get_license_type
```

Get license type. This is an integer representing GtkLicense described above. Example;

```
my Int $it = $dialog.get_license_type;  
say "License type: ", GtkLicense($it);
```

[gtk_about_dialog_] set_license_type

```
method gtk_about_dialog_set_license_type
```

Set license type. E.g.

```
$dialog.set_license_type(GTK_LICENSE_ARTISTIC);
```

[gtk_about_dialog_] get_website

```
method gtk_about_dialog_get_website
```

Get website.

[gtk_about_dialog_] set_website

```
method gtk_about_dialog_set_website
```

Set website.

[gtk_about_dialog_] get_website_label

```
method gtk_about_dialog_get_website_label
```

Returns the label used for the website link.

[gtk_about_dialog_] set_website_label

```
method gtk_about_dialog_set_website_label
```

Set website label.

[gtk_about_dialog_] get_authors

```
method gtk_about_dialog_get_authors
```

Get list of authors.

[gtk_about_dialog_] set_authors

```
method gtk_about_dialog_set_authors
```

Set authors.

[gtk_about_dialog_] get_artists

```
method gtk_about_dialog_get_artists
```

Get artists.

[gtk_about_dialog_] set_artists

```
method gtk_about_dialog_set_artists
```

Set artists.

[gtk_about_dialog_] get_documenters

```
method gtk_about_dialog_get_documenters
```

Get documenters.

[gtk_about_dialog_] set_documenters

```
method gtk_about_dialog_set_documenters
```

Set documenters.

[gtk_about_dialog_] get_translator_credits

```
method gtk_about_dialog_get_translator_credits
```

Get translator credits

[gtk_about_dialog_] set_translator_credits

```
method gtk_about_dialog_set_translator_credits
```

Set translator credits

[gtk_about_dialog_] get_logo

```
method gtk_about_dialog_get_logo
```

Get pixel buffer of logo.

[gtk_about_dialog_] set_logo

```
method gtk_about_dialog_set_logo ( OpaquePointer $logo-pixbuf )
```

Set the logo from a pixel buffer. E.g.

```
my GTK::V3::Gtk::GtkImage $logo .= new(  
  :filename(%?RESOURCES<library-logo.png>.Str)  
);  
$about-dialog.set-logo($logo.get-pixbuf);
```

[gtk_about_dialog_] get_logo_icon_name

```
method gtk_about_dialog_get_logo_icon_name
```

Get name of logo icon.

[gtk_about_dialog_] set_logo_icon_name

```
method gtk_about_dialog_set_logo_icon_name
```

Set name of logo icon.

[gtk_about_dialog_] add_credit_section

```
method gtk_about_dialog_add_credit_section
```

Add credit section.

new

```
multi submethod BUILD (:empty!)
```

Create an empty about dialog

```
multi submethod BUILD (:widget!)
```

Create an about dialog using a native object from elsewhere. See also `Gtk::V3::Glib::GObject`.

```
multi submethod BUILD (:build-id!)
```

Create an about dialog using a native object from a builder. See also `Gtk::V3::Glib::GObject`.